



Radiant Cove Heater

RCG Series

Features

Color

- Silichem off-white.

Voltage

- 240V, 50/60 Hz.

Construction

- Front made of an aluminum extrusion profiled to increase radiating surface.¹
- Back of the unit made with 18-gauge steel.
- Junction box on each end.
- Wall installation brackets (supplied) that doesn't require opening the unit's casing.²
- KOE 7/8 in. (22 mm) for the installation of the BX wires.³
- 4 in. (102 mm) ground wires on both ends.³
- Highly-emissive paint on the heat exchanger for higher efficiency.

Heating element

- Stainless steel tubular heating element inserted into a solid aluminum extrusion preventing any thermal expansion noise.

Control

- Global Commander highly recommends to use an electronic wall thermostat for greater comfort. (Not offered by Global Commander)

Installation

- 6 ft. (1.83 m) minimum clearance to floor and 4 1/2 in. (114 mm) minimum from ceiling.

Warranty

- 10-year warranty against defects.

Application

- Entrance way, bathroom, kitchen, living room, family room, bedroom, patio door, bay window, daycare, nursery, workshop.

Models

Product #	Watts	Product Length		Net Weight		Gross Weight		Packaging Dimensions					
		in.	mm	lb	kg	lb	kg	A		B		C	
								in.	mm	in.	mm	in.	mm
RCGU0390BL	390	34	864	6	2.7	7.3	3.2	37.0	939.8	3.75	95.5	6.25	158.8
RCGU0600BL	600	47	1194	8	3.6	9.4	4.1	49.75	1263.6	3.75	95.5	6.25	158.8
RCGU0750BL	750	59	1499	10	4.5	11.7	5.0	61.5	1562.1	3.75	95.5	6.25	158.8
RCGU0900BL	900	71	1803	12	5.4	14.0	6.4	73.75	1873.3	3.75	95.5	6.25	158.8
RCGU1050BL	1050	83	2108	13	5.9	16.0	7.3	85.0	2159.0	3.75	95.5	6.25	158.8
RCGU1200BL	1200	94	2388	15	6.8	18.1	8.2	96.5	2451.1	3.75	95.5	6.25	158.8
RCGU1500BL	1500	113	2870	18	8.2	21.6	9.5	115.0	2921.0	3.75	95.5	6.25	158.8

Standard color is silichem off-white.

